



Acoflex Eje Directo. Serie A

Acoflex Shaft to Shaft. A Series

Mod. A		A00	A0	A1	A2	A3	A4	A5	A6	A7	A8	A9	A10
Par Nominal [Nm] Nominal Torque		6.5	20	50	100	200	400	1000	2000	4000	7500	12500	25000
Par Max [Nm] Max Torque		20	50	90	250	500	1000	2500	4000	8000	15000	25000	40000
Velocidad Max [rpm] Max Speed		10000	9000	8000	6500	4800	3500	2900	2500	2200	1850	1600	1250
Momento de Inercia [Kgm ²] Moment of Inertia		-	-	0.001	0.005	0.012	0.05	0.155	0.437	0.825	2.325	4.95	12
Desplazamiento Axial [mm] Axial Misalignment		+0.5	+0.5	+1	+1	+1.5	+1.5	+2	+2	+2.5	+2.5	+3	+3
Desplaz. Lateral [mm] Lateral Misalign.		0.1	0.1	0.1	0.1	0.15	0.2	0.2	0.2	0.3	0.3	0.4	0.5
Desplaz. Angular [°] Angular Misalign.		1	1	1	1	1	1	1	1	1	1	1	1
Diametros [mm] Diameters	A	42.5	62	80	107	140	176	225	267	307	366	432	532
	B	32	50	64	80	86	110	140	180	205	242	280	330
	Ø Max Eje Shaft Ø Max	16	24	32	42	50	65	85	110	130	150	180	210
	Ø Pretaladrado Ø Preboring	6	8	14	17	19	24	29	39	48	62	73	96
Longitudes [mm] Lengths	K	14	18	24	34	45	55	63	73	81	91	102	123
	L	45	71	91	132	154	177	213	257	307	378	418	470
	M	17	27	34	46	55	61	75	92	113	144	158	180
	N	1	1	2	2	2	3	3	3	3	4	4	4
Masa [kg] Mass		0.3	0.9	1.8	4	7.5	14	28	52	80	145	215	350
Ref. Guarnición Insert Ref.		G00	G0	G1	G2	G3	G4	G5	G6	G7	G8	G9	G10