



Acoflex para casquillo cónico. Serie AT

Acoflex with taper bushing. AT Series

Mod. AT		A1T	A2T	A3T	A4T	A5T	A6T	A7T
Par Nominal [Nm] Nominal Torque		50	100	200	400	1000	2000	4000
Par Max [Nm] Max Torque		90	250	500	1000	2500	4000	8000
Velocidad Max [rpm] Max Speed		8000	6500	4800	3500	2900	2500	2200
Desplazamiento Axial [mm] Axial Misalignment		+1	+1	+1.5	+1.5	+2	+2	+2.5
Desplaz. Lateral [mm] Lateral Misalign.		0.1	0.1	0.15	0.2	0.2	0.2	0.3
Desplaz. Angular [°] Angular Misalign.		1	1	1	1	1	1	1
Diametros [mm] Diameters	A	80	107	140	176	225	267	307
	B	64	80	86	110	140	180	205
	Ø Max Eje Shaft Ø Max	28	32	42	50	75	90	110
	Ø Pretaladrado Ø Preboring	14	17	19	24	29	39	48
Longitudes [mm] Lengths	K	24	34	45	55	63	73	81
	L	91	132	154	177	213	257	307
	M	34	46	55	61	75	92	113
	N	2	2	2	3	3	3	3
Casquillo Bush		1108	1210	1610	2012	3020	3535	4545
Ref. Guarnición Insert Ref.		G1	G2	G3	G4	G5	G6	G7