



Acoplamiento para eje directo Serie M

Shaft to Shaft Coupling M Series

Mod. M		1	2	3	4	5	6	7	8	9	10	11	12	13
Par Nominal [Nm] Nominal Torque		10	30	60	100	220	450	600	900	1600	3000	5000	8500	12500
Par Max [Nm] Max Torque		30	50	200	250	600	1200	1600	2600	4700	8500	1400	25400	37000
Velocidad Max [rpm] Max Speed		4000	4000	4000	3000	3000	3000	2500	2500	2500	2000	1600	1250	900
Momento de Inercia [kgm ²] Moment of Inertia		-	-	0.01	0.04	0.1	0.2	0.3	0.8	3.0	3.0	4.9	9	31
Diametros [mm] Diameters	A	86	110	140	170	210	250	280	320	360	400	450	550	700
	B	30	39	48	58	80	95	110	125	140	160	180	205	275
	Ø Max Eje Shaft Ø Max	15	22	28	35	44	55	65	75	85	95	110	130	170
	Ø Pretaladrado Ø Preboring	-	-	-	-	18	22	25	30	30	35	60	75	90
Longitudes [mm] Lengths	L	50	115	136	157	178	198	220	240	260	300	350	430	520
	N	14	15	16	17	18	18	18	20	20	20	22	70	80
Masa [kg] Mass		0.8	2	3	6	12	20	29	40	56	82	130	215	402
Ref. Flector Tyre Ref.		12/15	16/22	23/28	29/35	36/44	45/55	56/65	66/75	76/85	86/95	96/110	111/130	131/140