

# ANTICONGELANTE F 30

Antifreeze of direct use

## DESCRIPTION

ANTICONGELANTE F-30 is a 100% organic fluid compounds of monoetilenglycol and anticorrosives additives. Exempt of borates, phosphate, nitrites and silicates.

## TYPICAL PHYSICAL CHARACTERISTICS

ESSAY	TYPICAL VALUE	METHODIQUE ESSAY
Aspect	Liquid limpido	HI-101
Colour	Yellow	HI-102
Density 15,5°C	1,05 Kg/l	ASTM D-1298
Freeze point	- 18°C	ASTM D-97
pH	8,2	HI-501
Flash point	n.a.	ASTM D-92

HI = Test developed by Houghton Ibérica

## APPLICATIONS

It is adequate to refrigerated closed system.

## HOW TO USE

ANTICONGELANTE F-30 is used in supplier state without dilute. To compensate water evaporations it needs to be used demineralised water or water with a low salt content.

## SHIPPING INFORMATION

ANTICONGELANTE F-30 is habitually supplied in boxes of 4 x 5 kg, drums of 25, 50, 185 kg and containers of 1000 kg.

• With license of HOUGHTON INTERNATIONAL INC.

Nº edition: 3

Revision Date: 01/11-J.J.C.



REFRIGERACIÓN ZELSIO, S.L.

C/ Montemayor, 2 Pta. 11 Der.

46950 Xirivella. Valencia (España)

Tel. +34 963 799 829 T.m. +34 699 096 497

info@zelsio.com www.zelsio.com



HOUGHTON™

Fluid Partnerships Making a World of Difference