

We have the solution...

...the future has a name



## Technical Information

## LUBRICANT CONSULT GMBH

Gutenbergstraße 13 · D-63477 Maintal – Germany · Telefon: +49-61 09 - 76 50-0 · Fax: +49-61 09 - 76 50-51 · Internet: [www.lubcon.com](http://www.lubcon.com)

### LUBCON 4S-FLUID



#### Immediate – cleaning – lubricating – conservating

#### LUBCON universal oil with PTFE

- LUBCON 4S-FLUID** is an universal applicable synthetic special oil with PTFE additives and excellent lubricating efficiency and long-term effect, for every sticking, stucking and squeaking object.
- LUBCON 4S-FLUID** suitable for cleaning and conservation of all lubricating points in the industry and craft, as well as in households, amateur mechanic and hobby area.
- LUBCON 4S-FLUID** looses rusty nuts as well as screws and improves gliding of hinges and locks.
- LUBCON 4S-FLUID** removes burn residues of sporting weapons and gives dirty objects a gleaming surface.
- LUBCON 4S-FLUID** is due to its excellent EP- and adhesion behaviour successful as chain oil in all industrial areas.
- LUBCON 4S-FLUID** displaces humidity, forms a moisture repellent protective film on metals, therefore increase of the electrical contact ability.
- LUBCON 4S-FLUID** protects from corrosion and rust due to its excellent adhesive behaviour.
- LUBCON 4S-FLUID** is used for conservation of various surfaces. It is silicone-free, therefore it does not attract dust and dirt.

#### Quality Features

- excellent penetrating ability and creeping behaviour
- good water displacement
- low friction moment and cold insulator
- silicone free, free of environmental loading heavy metals

#### Technical Data

#### 4S-FLUID

Colour	yellowish
Base	synthetic hydrocarbons
Viscosity DIN 51562 at +40 °C (mm <sup>2</sup> /s)	approx. 80
Density DIN 51757 at +20 °C (g/cm <sup>3</sup> )	approx. 0.89
Pourpoint DIN 51597 (°C)	approx. -50
Temperature service range (°C)	-50 up to + 150

#### Application

Manually, by drip-feed lubricator, brush or dipping or automatic Fluid – or dosage devices.

#### Original Packaging

12 x 250 ml Spray cans, 6 x 5 l cans, 20 l cans, 200 l one way drums

The products are subject to severe controls of manufacture and comply in full with the specifications set forth by our company. Due to the multitude of different influencing factors, we cannot assume any warranty for the successful in each case. Therefore, we recommend to perform field tests. We strictly refuse any liability.