



LUBCON KORROQUICK



Date of issue: 11.09.2013

KORROQUICK is a high valued rust loosener, a corrosion protection product and a lubricant, which is also fully effective on wet surfaces.

KORROQUICK is excellently suitable for the displacement of moisture and cleaning fluid.

KORROQUICK separates screw connections. It takes off rust film and dissolves high temperature scaling.

KORROQUICK is most efficient between -30° and +60°C. But Korroquick can be used up to approx. +150°C.

Special properties

- Excellent creeping properties
- Excellent dewatering properties
- Very good rust removing properties
- Very good separation effect
- Very good corrosion protection

Product Characteristics	Value	Dimension	Norm / Standard
Colour	brownish		
Density at 20°C	0,805	g/cm ³	DIN 51757
Operating temperature range	-30 to 150	°C	
Oil type	mineral oil		
Kinematic viscosity at 40°C	1,6	mm ² /s	DIN EN ISO 3104
Pour point	< -40	°C	DIN ISO 3016
Flash point	< -30	°C	DIN EN ISO 2592

Application

KORROQUICK can be used in all industrial areas.

Packaging units

12 x 400 ml spray cans, 20 l canister, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>