

Enfriador de botellas
Bottles cooler

				
BE-100-I 143001900500	BE-150-I 143001000500	BE-200-I 143001100500	BE-250-I 143001200500	BE-300-I 143001300500
	BE-150-A 143001400500	BE-200-A 143001500500	BE-250-A 143001600500	
BE-100-EA 143002000500	BE-150-EA 143001400575	BE-200-EA 143001500575		

Características Técnicas
Technical Data

REF. REF.	LARGO LENGHT	ALTO HEIGHT	FONDO DEPTH	POTENCIA FRIG FRIG POWER	CONSUMO CONSUMPTION	CAPACIDAD CAPACITY	PESO NETO NET WEIGHT	PUERTAS DOORS	SEPARADORES SHELVES	TENSIÓN MONOFÁSICA SINGLE PHASE VOLTAGE	REFRIGERANTE COOLANT
BE-100	1010 mm	850 mm	550 mm	200 W	210 W	270 L	61 Kg	2 ud	1 ud	220 V - 50/60 Hz	R-134a
BE-150	1500 mm	850 mm	550 mm	250 W	350 W	420 L	77 Kg	3 ud	2 ud	220 V - 50/60 Hz	R-134a
BE-200	1990 mm	850 mm	550 mm	300 W	396 W	580 L	96 Kg	4 ud	3 ud	220 V - 50/60 Hz	R-134a
BE-250	2480 mm	850 mm	550 mm	590 W	615 W	720 L	115 Kg	5 ud	4 ud	220 V - 50 Hz	R-134a
BE-300	2970 mm	850 mm	550 mm	680 W	615 W	860 L	134 Kg	6 ud	4 ud	220 V - 50/60 Hz	R-134a

Características Técnicas
Characteristics

- BE-I:
 - Exterior en acero inox. AISI-304 18/10, excepto el respaldo.
 - Interior en acero inox. AISI-304 18/10.
- BE-A:
 - Exterior en acero inox. AISI-304 18/10, excepto el respaldo.
 - Interior en aluminio.
- BE-100-EA:
 - Exterior en acero plastificado blanco, excepto el respaldo.
 - Interior en acero galvanizado.
- Separadores interiores de alambre en acero plastificado.
- Apoyos inox. regulables en altura.
- Cuadro de mandos y rejilla ventilación motor, de apertura frontal pivotante.
- Unidad condensadora ventilada y extraíble.
- Aislamiento de poliuretano inyectado, libre CFCs, densidad 40 Kg.
- Evaporador estático.
- Control de temperatura.
- Interruptor general ON - OFF luminoso.
- Temperatura de trabajo: +2°C +8°C a 32°C temperatura ambiente.

- BE-I:
 - AISI-304 18/10 stainless steel exterior, except rear panel.
 - AISI-304 18/10 stainless steel interior.
- BE-A:
 - AISI-304 18/10 stainless steel exterior, except rear panel.
 - Aluminium interior.
- BE-100-EA:
 - Plasticized steel exterior, except rear panel.
 - Galvanized interior.
- Inner vertical shelves of laminated steel wire.
- Height-adjustable stainless steel supports.
- Switch panel and ventilating motor grille with pivoting front opening.
- Ventilated, pull-out condenser unit.
- Injected polyurethane insulation, CFC friendly, 40 kg in density.
- Static evaporator.
- Temperature control.
- Luminous main switch ON - OFF.
- Working temperature: +2° +8° at 32° ambient temperature.

OPCIONES
OPTIONS

- Ruedas
- Motor lado izquierdo

- Castors
- Left side motor



BE-200



BE-100



BE-100-EA

