



Armario eurosneck, refrigeración contenedores

Eurosneck cabinet, containers chiller



AP - 400





AP - 400
142221000555

Características Técnicas

Technical Data

REF.	LARGO LENGHT	ALTO HEIGHT	FONDO DEPH	POTENCIA FRIG FRIG POWER	CAPACIDAD CAPACITY	PESO NETO NET WEIGHT	ESTANTES SHELVES	PUERTAS PEQ. SMALL DOORS	PUERTAS GRA. LARGE DOORS	TENSIÓN MONOFÁSICA SINGLE PHASE VOLTAGE	REFRIGERANTE COOLANT	TEMPERATURA TRABAJO WORKING TEMPERATURE
AP-400	600 mm	1880 mm	650 mm	300 W	400 L	95 Kg	5 ud	0	1	220 V - 50/60 Hz	R-134a	-4°C+4°C

Características Técnicas

Characteristics

- Exterior en acero inox AISI-304 18/10, excepto el respaldo.
- Interior en acero inox AISI-304 18/10, con aristas curvas.
- Puertas con sistema de cierre automático y burlete magnético, la puerta permanece abierta al superar los 90° de apertura, reversible.
- Contrapuerta inox embutida
- Luz interior
- Estantes interiores de alambre en acero plastificado,
- 5 cajones plásticos 410 x 480 x 140
- Pies en tubo de acero inox ajustables en altura 125 - 200 mm.
- Cuadro de mandos y rejilla ventilación motor, desmontable.
- Unidad condensadora ventilada.
- Evaporador sistema tiro forzado, con recubrimiento anticorrosión.
- Evaporación automática del agua de descarche.
- Aislamiento de poliuretano inyectado, libre de CFCs, densidad 40 Kg.
- Control digital de temperatura y descarches.

- AISI-304 18/10 stainless steel exterior, except rear panel.
- AISI-304 18/10 stainless steel interior with sanitary edge.
- Doors with automatic closing system and magnetic gasket, door stays open when opening over 90°, reversible.
- Inox rear door pressed panel
- Internal lighting.
- Plastic coated steel wire shelves
- 5 plastic containers 410x480x140
- Adjustable 125 - 200 mm tubular stainless steel feets.
- Detachable switch panel and ventilating motor grille.
- Ventilated condenser unit.
- Forced draught system evaporator with corrosion-resistant coating.
- Defrost water automatic evaporation.
- Injected polyurethane insulation, CFC friendly , 40 kg in density.
- Temperature and deforst digital control.

OPCIONES

OPTIONS

- Cerraduras
- Ruedas
- Registrador de alarmas HACCP
- Conexión a PC
- Barras carniceras

- Locks
- Castors
- HACCP alarma recorder
- PC conection
- Butcher's bars