





Refrigerador horizontal para botellas

Back-bar bottles cooler

			
ERH-150 141211100500	ERH-250 141211200500	ERHS-250 141211210500	ERH-350 141211300500
NRH-150 141211100505	NRH-250 141211200505		NRH-350 141211300505

Características Técnicas

Tecnical Data

REF. REF.	LARGO LENGHT	ALTO HEIGHT	FONDO DEPTH	POTENCIA FRIG FRIG POWER	CONSUMO CONSUMPTION	CAPACIDAD BOT. BOT. CAPACITY	ESTANTES SHELVES	PUERTAS ABT. FRONT OPEN DOORS	PUERTAS DES SLIDING DOORS	TENSIÓN MONOFÁSICA SINGLE PHASE VOLTAGE	REFRIGERANTE COOLANT
ERH-150	600 mm	900 mm	520 mm	185 W	200 W	96 ud	2 ud	1	0	220 V - 50/60 Hz	R-134a
ERH-250	905 mm	900 mm	520 mm	250 W	260 W	156 ud	2 ud	2	0	220 V - 50/60 Hz	R-134a
ERHS-250	905 mm	900 mm	520 mm	250 W	260 W	156 ud	2 ud	0	2	220 V - 50/60 Hz	R-134a
ERH-350	1355 mm	900 mm	520 mm	300 W	310 W	240 ud	2 ud	3	0	220 V - 50/60 Hz	R-134a
NRH-150	600 mm	900 mm	520 mm	185 W	200 W	96 ud	2 ud	1	0	220 V - 50/60 Hz	R-134a
NRH-250	905 mm	900 mm	520 mm	250 W	260 W	156 ud	2 ud	2	0	220 V - 50/60 Hz	R-134a
NRH-350	1355 mm	900 mm	520 mm	300 W	310 W	240 ud	2 ud	3	0	220 V - 50/60 Hz	R-134a

Características Técnicas

Characteristics

- Exterior en acero galvanizado plastificado negro.
- Interior en chapa de acero plastificado.
- Estantes de alambre de acero plastificado.
- Aislamiento de poliuretano inyectado ecológico libre CFCs, densidad 40 Kg/m³.
- Puerta de vidrio con doble acristalamiento, sobre bastidor de aluminio anodizado con tirador.
- ERH: puertas cristal apertura frontal.
- ERHS: dos puertas cristal correderas.
- Especialmente diseñados para bebidas y productos envasados.
- Control de temperatura.
- Evaporación automática del agua de descarche.
- Iluminación interior.
- Equipo frigorífico:
Temperatura de trabajo: +4°C +8°C a 26°C temperatura ambiente.
Compresor: hermético, de alto par de arranque.
Evaporador: ventilado impreso en placa de aluminio.
Condensador: ventilado libre de mantenimiento.
- **NRH: Puertas ciegas apertura frontal.**

- *Galvanized plasticised steel exterior black color.*
- *Plasticised steel sheet interior.*
- *Plasticised steel wire shelves.*
- *Ecologic injected polyurethane insulation, CFCs free, density of 40 Kg/m³.*
- *Double glazing door, on anodized aluminium framework.*
- *ERH: frontal opening glass doors.*
- *ERHS: two sliding glass doors.*
- *Specially designed for bottled drinks.*
- *Temperature control.*
- *Defrost water automatic evaporation.*
- *Interior lighting.*
- *Refrigerating equipment:*
Work temperature: +4°C +8°C with 26°C ambient temperature
Compressor: Hermetic, thermal protection
Evaporator: Ventilated, printed on aluminium sheet
Condenser: maintenance - free, ventilated
- **NRH: Frontal opening blind doors.**

OPCIONES

OPTIONS

· Pantalla publicitaria

· Cerradura (ERHS)

· *Publicity screen*

· *Lock (ERHS)*



ERH-250



ERH-350



NRH-250



ERH-150



ERHS-250